


# PRODRUT®

Przedsiębiorstwo PRODRUT® Sp. z o.o.

44-100 Gliwice, ul. Sobieskiego 11



## CORED WIRE

Catalogue sheet No. **02**

<b>Grade</b>	<b>C</b>	
<b>Wire diameter:</b>	<b>Ø 13 mm</b>	
<b>Tiny wall - pipe material:</b>	low-carbon steel band - thickness 0,4 mm Attention : Allowable thickness 0,35 mm	
<b>Core chemical composition:</b>		% MIN
		% MAX
	<b>C</b>	98,0
	<b>S</b>	0,5
	<b>H<sub>2</sub>O</b>	0,5
<b>Filling:</b>	160 ± 8 g / m	
<b>Finished coil parameters:</b>		
inner diameter of coil	600 <sup>+10</sup> mm	
outer diameter of coil	max 1350 mm	max 800 mm
coil width	800 <sup>+20</sup> mm	400 <sup>±20</sup> mm
coil wire length	1000 ÷ 5700 m	500 ÷ 1800 m
coil total weight	500 ÷ 2200 kg	250 ÷ 600 kg
<b>Packing:</b>	on wooden pallets, in steel baskets or loose, axle of coil - horizontal or vertical	
<b>Marks:</b>	identifier of coil and finished product tag	
<b>Storage:</b>	covered and dry rooms protected against atmospheric conditions	
<b>Transportation:</b>	covered means of transport	
<b>Application:</b>	accurate correction of chemical composition considering carbon contents carburization	
<i>Real parameters of wire for each coil are enclosed with finished product tag. This sheet is valid since 30 April 2006</i>		



ISO 9001:2000

REGON:003528687

KRS: 0000145618

NIP: 631-000-02-85

BANK: ING Bank Śląski S.A. O/Gliwice

2710501285100000202116448 (PLN)

57105012851000002286303983 (EUR)

38105012981000002298106770 (USD)

Kapitał zakładowy: 100.000,00 zł (wpłacony w całości)

**Siedziba Spółki**

ul. Sobieskiego 11

44-100 Gliwice

telefon/fax:(48) 32 2308428

telefon: (48) 32 2345513

http: [www.prodrut.pl](http://www.prodrut.pl)

e-mail: [prodrut.tech@prodrut.pl](mailto:prodrut.tech@prodrut.pl)

**Zakład Produkcyjny**

ul. Piotra i Pawła 1

72-015 Police

telefon: (48) 91 3172929

fax: (48) 91 3172448